



## Touch Metal Piezo Switch

### Description

Touch Metal Piezo Switch, 18.6mm mounting diameter, PG-11 thread, 22mm flat actuation area with either continuous (SBA1C) or toggle (SBA1T) function. Metal housings are milled, one piece construction and mounted with a nut. Aluminum housings are available in Silver, Red, Black, Green, Gold or Blue anodization.

### Approvals

- MIL-STD - 810C, 202E, 461B, 462
- CE - EVERSWITCH products comply with Directives 2006/95/EEC for low voltage components.
- IP Rating – IP69K Compatible with IEC 60529; EN 60529
- EMC: Directive 2004/108/EWG

### Characteristics

- Function: Continuous or Toggle (on/off)
- Proven Reliability: Tested for 50,000,000 cycles
- Weatherproof: Used in harshest outdoor conditions
- Touch Activated: Operable with gloves, tools, etc.
- Sterilizable: Wash down proof up to 100 BAR
- Vandal Resistant: For use in high traffic and abusive areas
- Zero power required for keypad operation
- Mimics a dry contact switch closure
- Eliminates RFI, EMI and ESD issues
- Five year warranty

### Customized Options

A wide range of design options are available: connectors, switch function (timer, N.C. and programmable types), current rating (up to 10A), graphics and housing dimensions and materials. We offer an embedded CPU for data output compatible with various communication protocols.

## TECHNICAL DATA

### Electrical Data

Switch Function SBA1C	N.O. up to 30sec std.
Switch Function SBA1T	On/Off Alternating
Switch Voltage	1-24V AC/DC
Switching Current	0.2A std (0.5A option)
Rated Breaking Capacity	1W
Operating Cycles	>50,000,000
Switch Resistance OFF	> 5 MΩ
Switch Resistance ON	< 20 Ω
Capacity	30 pF
Contact Configuration	Free polarity

### Mechanical Data

Housing Materials	Aluminum 6061 T651 or Stainless Steel (303/304)
Actuating Force	3-5 Newton
Connection	4 wires 24 AWG
Actuating Travel	0.002 mm
Shock Protection	IK 06
Fastening Torque	2.5 Nm

### Environmental Data

Operating Temperature	-40 to +125 °C
Storage Temperature	-40 to +125 °C
IP-Protection	IP69K (front and back)