



## MODULAR JACKS AND PLUGS: GAX Series

### Right Angle Ganged Jack

#### Product Features

- Available in 6 and 8 Position Housings
- Right Angle Version
- Ribbed Pin Guides
- Metal Locking Brackets
- CSA/NRTL Certified File No. LR78160

#### Performance Specifications

##### Materials and Finish

##### Housing Material

Thermoplastic, UL 94V-0 Rated, Gray Color

##### Contact Material

Phosphor Bronze

#### Electrical Characteristics

##### Insulation Resistance

500 Megohms Min.

##### Dielectric Withstanding Voltage

1000V AC RMS for 1 Minute

##### Contact Resistance

20 milliohms Max.

##### Current Rating

1.5A

##### Voltage Rating

125V DC

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

#### Generated Part Number



#### Part Number Builder

<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Series	No. of Ports	No. of Positions	Plating Option

#### Series

GAX - Right Angle PCB Mount

#### Number of Ports

- 2 - 2 Port
- 3 - 3 Port
- 4 - 4 Port
- 5 - 5 Port (Available Only With 6 Positions)
- 6 - 6 Port (Available Only With 6 Positions)
- 7 - 7 Port (Available Only With 6 Positions)
- 8 - 8 Port (Available Only With 6 Positions)

#### Number of Positions / Contacts

- 62 - 6 Positions / 2 Contacts
- 64 - 6 Positions / 4 Contacts
- 66 - 6 Positions / 6 Contacts
- 88 - 8 Positions / 8 Contacts

#### Plating Option

- Blank - Gold Flash
- 50 - 50µ" Gold Plating

Contact Kycon for Other Options

#### GAX Series

Dimensions in mm

