

## MODULAR JACKS AND PLUGS:

### GDWLX Series

Vertical PCB Mount

#### Product Features

Easy Viewing LEDs to Act as Power/Transmit Indicators

Available Fully Shielded for EMI/RFI Protection

Available Through Hole

CSA/NRTL Certified File No. LR78160

#### Performance Specifications

##### Materials and Finish

##### Housing

##### Housing Material

PBT Thermoplastic, Glass Filled, UL 94V-0 Rated,  
Black Color

##### Contact Material

Phosphor Bronze

##### Shield Material

Copper Alloy, Nickel Plated

#### Electrical Characteristics

##### Insulation Resistance

500 Megohms Min.

##### Dielectric Withstanding Voltage

1000V rms, 60Hz

##### Contact Resistance

20 milliohms Max.

##### Current Rating

1.5A

Voltage Rating


125V DC

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

#### Generated Part Number



#### Part Number Builder



#### Series

GDWLX - Vertical PCB Mount Modular Jack

#### Shield Option

PNS - Shielded

#### Number of Positions/Contacts

88 - 8 Positions / 8 Contacts

#### LED Color

G/G - Green, Green

G/GY - Green, Green - Yellow

G/R - Green, Red

G/Y - Green, Yellow

Y/G - Green, Yellow

Contact Kycon for Other Options

#### GDWLX Series

Dimensions in mm

