



## MODULAR JACKS AND PLUGS: GLX Series

### Right Angle Modular Jack

#### Product Features

- 0.570" Height
- Snap-In Board Retention Tabs
- Available in 4, 6, 8 and 10 Position Housings
- CSA/NRTL Certified File No. LR78160
- UL File No. E134345

#### Performance Specifications

##### Materials and Finish

###### Housing Material

PBT Thermoplastic, UL 94V-0 Rated

###### Contact Material

Phosphor Bronze

#### Electrical Characteristics

##### Insulation Resistance

500 Megohms Min.

##### Dielectric Withstanding Voltage

1000V RMS, 60Hz

##### Contact Resistance

20 milliohms Max.

##### Current Rating

1.5A

##### Voltage Rating

125V DC

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

#### Generated Part Number



#### Part Number Builder

<input type="text"/>	-	<input type="text"/>	<input type="text"/>	<input type="text"/>
Series		Shield Option	Positions & Contacts	Other Option

#### Series

GLX - Right Angle Modular Jack

#### Shield Options

- A - Non-Shielded with Panel Stops
- N - Non-Shielded without Panel Stops

#### Number of Positions / Contacts

- 44 - 4 Positions / 4 Contacts
- 64 - 6 Positions / 4 Contacts
- 66 - 6 Positions / 6 Contacts

#### Other Option

##### Plating Option

- Blank - Gold Flash
- 50 - 50µ" Gold Plating

#### Color Option

- Blank - Gray
- BLK - Black

Contact Kycon for High Temperature and Other Options

#### GLX Series

Dimensions in mm

#### GLX-A-44xx

