



MODULAR JACKS AND PLUGS: GWX /GWX-SMT Series Right Angle Modular Jack, Tab Up

Product Features:

- Low Profile Design Suitable for PC Add-on
- Tab up Design for Easy Insertion/Removal of Mating Plug
- Available Fully Shielded for EMI/RFI Protection
- Available with Through Hole or Surface Mount
- Contact Options
- CSA/NTRL Certified File No. LR78160

Performance Specifications

Materials and Finish

Housing

High Temperature Thermoplastic, UL 94V-0 Rated, Black Color

Contact Material

Phosphor Bronze

Contact Plating

Standard: Nickel Underplating, Selectively Plated Gold Flash

50 Option: Nickel Underplating, Selectively Plated 50µ" Gold

Contact Area, Gold Flash on Solderails

Shield Material

Copper Alloy, Nickel Plated

Electrical Characteristic

Insulation Resistance

500 Megohms Min.

Rated Voltage

125V DC

Contact Resistance

20 milliohms Max.

Rated Current

1.5A

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

Part Number Builder

<input type="text"/>	-	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Series		Shield Option	No. of Positions & Contacts	Plating Options	Packaging Option

Series

- GWX - Through Hole, Right Angle
- GWX-SMT - Surface Mount, Right Angle

Shield Option

- N - Non-Shielded
- S - Fully Shielded
- S3 - Fully Shielded with Tabs on Top (Available only with Through Hole)
- S9 - Fully Shielded with Tabs on Top and Sides

Number of Positions/Contacts

88 - 8 Positions / 8 Contacts

Plating Option

- Blank - Gold Flash
- 50 - 50µ" Gold Plating

Packaging Option

- Blank - Tray
- TR - Tape & Reel (Available only with SMT Option)

Contact Kycon for Other Options

GWX-S-88

Dimensions in mm

