




D-SUBMINIATURE CONNECTORS:
K202XHT Series
 Right Angle Surface Mount

K202XHT Series Dimensions
 Dimensions in mm



Shell Size	In mm				
	A	A1	B	C	D
9 (E)	±.010 ±0.25	±.010 ±0.25	±.005 ±0.13	±.015 ±0.38	±.005 ±0.13
15 (E)	.643 16.33	N/A	.984 24.99	1.213 30.81	.609 15.46
25 (B)	1.511 38.38	1.534 38.96	1.852 47.04	2.088 53.04	1.498 38.06

A = Exterior of Female Shell (S)
 A1 = Interior of Male Shell (P)

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

Part Number Builder

-
 Series Shell Size Contact Contact Type Mounting Option Plating Option

Series

K202XHT - D-Subminiature Connector, Right Angle, Ultra Short Footprint, Surface Mount, Reflow Compatible

Shell Size-Contact Option

- E - 9 Contacts
- B - 25 Contacts
- E - 15 Contacts, High Density (Socket only)

Contact Type

- P - Pin Contact (Plug)
- S - Socket Contact (Receptacle)

Mounting Option

- N - With Boardlocks and #4-40 UNC Threaded Inserts
- NJ - With Boardlocks and JSX-1055 Jackscrews Installed

Plating Option

- Blank - Gold Flash
- 15 - 15µ" Gold
- 30 - 30µ" Gold

Contact Kycon for Tape and Reel and Other Options