



2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number



Part Number Builder

<input type="text"/>	-	<input type="text"/>	<input type="text"/>	<input type="text"/>
Series		Type	Insulator Color	Packaging

Series

KUSBX-SMT3 - USB Type C Socket, Right Angle SMT contacts, Long Shield Pins

Type

CS - C Type

Insulator Color Option

B - Black

Packaging

TR - Tape and Reel

Contact Kycon for more options

UNIVERSAL SERIAL BUS: KUSBX-SMT3 Series

USB Type C Socket, Right Angle, SMT Contacts

Long Shield Pins

Product Features

USB Version 3.1

Gen 2 (10Gbps)

SMT Contact

Long Shield Pins

Performance Specifications

Materials and Finish

Housing

High Temperature Thermoplastic, UL94V-0 Rated

Shield

Stainless Steel, Nickel Plated

Contact Material

Copper Alloy

Contact plating

Gold Flash on Contact Area

All over Nickel Underplate

Electrical Characteristics

Rated Current

5.0A

Rated Voltage

30V

Insulation Resistance

100 Megohms Min. at 250V DC

Contact Resistance

30 milliohms Max.

Dielectric Withstanding Voltage

100V AC RMS For 1 Minute

Mechanical Characteristics

Insertion Force: 2kgf MAX.

Withdrawal Force: .8kgf MIN.

Durability: 10000 Mating Cycles Min.

Operating Temperature

-40°C to +85°C

KUSBX-SMT3

Dimensions in mm

