



**AUDIO JACKS: STX-35332 Series**  
Surface Mount 3.5mm Audio Jack

**Product Features**

Offered in a 3-Pole Version  
Used in Devices Such as Audio Equipment, Cell Phones, or Digital Still Camera  
Complies with EIA Standards  
CSA/NRTL Certified File No. LR78160

**Performance Specifications**

**Materials and Finish**

**Housing**  
High Temperature Thermoplastic, UL 94V-0 Rated

**Terminals**

Copper Alloy, Gold Plated

**Electrical Characteristics**

**Contact Resistance Before Durability Test**

50 milliohms Max.

**After Durability Test**

100 milliohms Max.

**Insulation Resistance**

100 Megohms Min. at 500V DC

**Dielectric Withstanding Voltage**

500V AC RMS for 1 Minute

**Operating Temperature**

-25°C to + 70°C

|                       |                     |                      |                  |
|-----------------------|---------------------|----------------------|------------------|
| 2D Drawing            | IGES                | STEP                 | 3D PDF           |
| Solder Profile        | CofC RoHS Compliant | CofC REACH Compliant | UL Plastic File  |
| Certificate of Origin | Check Stock         | Request a Sample     | Send Us An Email |

Generated Part Number

Part Number Builder

-     
 Series      Number of Pins      Threading Option      Packaging

**Series**

STX-35332 - Surface Mount 3.5mm Audio Jack

**Number of Pins**

- 3 - Pins
- 4 - Pins
- 5 - Pins

**Threading Option**

N - Non-Threaded Barrel

**Packaging**

TR - Tape and Reel

Contact Kycon for other options

**STX-35332**

Dimensions in mm

**STX-35332-3N-TR**

