

Telephone Jacks



			Overall	Overall	Overall	Contact	Contact
Item #	Item Name	Conductors	Width	Height	Length	Diameter	Length
	Telephone In-Line						
TJ-101	Jack	4	0.625 in	0.625 in	2.234 in	0.285 in	N/A
	Telephone In-Line						
TJ-105	Jack	5	0.625 in	0.625 in	2.375 in	0.285 in	N/A
	Telephone In-Line	_					
TJ-106	Jack Biaxial Shielded	6	0.750 in	1.500 in	2.609 in	0.285 in	N/A
TI 406 DN4	Telephone Jack		4 2 4 4 .	4.500:	4.766	0.205	/.
TJ-106 PM	Biaxial Shielded	6	1.344 in	1.500 in	1.766 in	0.285 in	N/A
TI 400	Biaxial Shielded		0.750 :	4.500 :	2 600 :	0.205 :	N1 / A
TJ-108	Telephone Jack	8	0.750 in	1.500 in	2.609 in	0.285 in	N/A
TI 400 DN4	Biaxial Shielded		4 244 :	4.500 :	4.700 :	0.205 :	N1 / A
TJ-108 PM	Telephone Jack	8	1.344 in	1.500 in	1.766 in	0.285 in	N/A
TI 101	Telephone In-Line		0.625 in	0.635 :-	2 224 :	0 30F in	NI/A
TJ-101	Jack	4	U.025 If1	0.625 in	2.234 in	0.285 in	N/A
TJ-120	Flanged Rear- Mounted Jack	4	0.625 in	1.188 in	1.125 in	0.285 in	0 100 in
13-120	Flanged Rear-	4	0.025 111	1.100 111	1.125 111	0.265 111	0.188 in
	Mounted Jack with						
TJG-120	Switches	5	0.625 in	1.188 in	1.312 in	0.285 in	0.375 in
110-120	Threaded Front-		0.023 111	1.100 111	1.312 111	0.285 111	0.373111
	Mounted Jack with						
TJGT-120	Switches	5	0.719 in	0.719 in	1.312 in	0.285 in	0.375 in
1301 120	Telephone Jack		0.7 13 111	0.713 111	1.512 111	0.203 111	0.373 111
TJS-102	Switch	4	1.625 in	2.156 in	2.359 in	0.285 in	N/A
	Telephone Jack					0.200	,//
TJS-105	Switch	5	1.625 in	2.156 in	2.359 in	0.285 in	N/A
	Telephone Jack	-					,
	Switch Biaxial						
	Shielded with						
TJS-106	Clothing Clip	6	2.281 in	2.000 in	2.641 in	0.285 in	N/A
	Telephone Jack						
TJS-108	Biaxial Shielded	8	2.281 in	2.000 in	2.641 in	0.285 in	N/A
	Flanged Rear-						
	Mounted Jack with						
TJS-120	Switches	5	0.625 in	1.188 in	1.312 in	0.285 in	0.375 in
	Telephone Jack Two						
	Switches Biaxial						
TJSS-106	Shielded	6	1.047 in	1.969 in	2.609 in	0.285 in	N/A
	Telephone Jack						
TJSS-108	Biaxial Shielded	8	1.047 in	1.969 in	2.609 in	0.285 in	N/A
	Threaded Front-						
	Mounted Jack with	_					
TJST-120	Switches	5	0.719 in	0.719 in	1.312 in	0.285 in	0.375 in



	Threaded Telephone						
TJT-102	Jack	4	0.719 in	0.719 in	1.391 in	0.285 in	N/A
	Threaded Telephone						
TJT-105	Jack	5	0.688 in	0.688 in	1.563 in	0.285 in	N/A
	Threaded Front-						
TJT-120	Mounted Jack	4	0.719 in	0.719 in	1.125 in	0.285 in	0.188 in
	Threaded Telephone						
TJT-125	Jack	5	0.750 in	0.750 in	1.281 in	0.285 in	N/A