



## (0.635 mm) .025" PITCH • RUGGED HERMAPHRODITIC CONNECTORS




10, 20, 30, 40, 50



LEAD STYLE	A	В
-01	(4.45) .1752	(1.59) .0628
-02	(7.45) .2933	(4.59) .1808
-03	(5.45) .2146	(2.59) .1021

Specify LEAD = Gold flash STYLE on contact. Matte Tin on tail from chart =10 µ" (0.25 µm) Gold on contact, Matte Tin on tail







= Vertical

-DH

= Right-angle

(Lead style -01 only)

**-K** = (3.50 mm) .138" DIA Polyimide film Pick & Place Pad

-TR = Tape & Reel

**-FR** = Full Reel Tape & Reel (must order maximum quantity per reel; contact Samtec for quantity breaks)

LEAD STYLE	MATED HEIGHT *
-01 & -01	(6.00) .236
-01 & -03	(7.00) .276
-03 & -03	(8.00) .315
-01 & -02	(9.00) .354
-02 & -03	(10.00) .394
-02 & -02	(12.00) .472

\*Processing conditions will affect mated height.

= Tape &

Reel

-FR

= Full Reel

Tape & Reel (must order

maximum quantity per reel; contact Samtec for quantity

breaks)

= (3.50 mm) .138" DIA Polyimide film Pick &

Place Pad

## (0.80 mm) .0315" PITCH • RUGGED HERMAPHRODITIC CONNECTORS



= Gold flash

on contact,

Matte Tin on tail

=10 μ" (0.25 μm) Gold on contact,

Matte Tin on tail

View complete specifications at: samtec.com?LSS

10, 20, 30, 40, 50




	LEAD STYLE	A
	-01 (-DH only)	N/A
	-03.0	(4.45) .175
3	-04.0	(5.45) .215

**STYLE** 

from

chart



Note: Some lengths, styles and options are non-standard, non-returnable.





No. of positions x (0.80) .0315 + (4.40) .173
788888888888888888888

B	→ (4.98) .196
	B

-DV

LEAD STYLE	MATED HEIGHT *
-03.0 & -03.0	(6.00) .236
-03.0 & -04.0	(7.00) .276
-04.0 & -04.0	(8.00) .315
-03.0 & -06.0	(9.00) .354
-04.0 & -06.0	(10.00) .394
-06.0 & -06.0	(12.00) .472

<sup>\*</sup>Processing conditions will affect mated height.

View complete specifications at: samtec.com?LSEM