



3D Step-file available on request



344S1G1G71NB

348811R1R50UB

Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Lens with.. Linse mit.. Lentille avec..	Light source Lichtquelle Source lum.		Voltage Spannung Tension			
	Protection Schutzart Protection	Surface Oberfläche Surface			LED Ø 5mm	Code	V	mA		
343 LED terminals LED-Anschlüsse Fils des LED's	4	IP64	B Brass, blackened Messing, geschwärzt Laiton, noirci	1 5 Stainless steel Edelstahl 1.4305 Acier inoxydable 5 Stainless steel Edelstahl 1.4305 Acier inoxydable 	A1 Amber Orange Orange	Y54U 7'000 mcd	 Yellow Gelb Jaune	0	without ohne sans	
	7	IP67	S Brass, nickel plated Messing, vernickelt Laiton, nickelé		B1 Blue Blau Bleu	Y50U 3'000 mcd		A	5	20
	8	IP68	5 Stainless steel Edelstahl Acier inoxydable		C1 Clear Klar Clair	Y501 80 mcd		B	12	20
			6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci		G1 Green Grün Vert	B91G 9'000 mcd		 Blue Blau Bleu	D	24
344 Faston 2.8 x 0.5	8	IP68	9 Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**	R1 Red Rot Rouge	B21G 2'120 mcd	 Red Rot Rouge	E		28	20
				W3 White Weiss Blanc	B61G 1'160 mcd		CL	9-48	20	
	4	IP64	1 Brass, blackened Messing, geschwärzt Laiton, noirci	1	A1 Amber Orange Orange	R54U 7'000 mcd	 Red Rot Rouge	CL1	5-28	20
					B1 Blue Blau Bleu	R50U 3'000 mcd				
348 Stranded wire Litze Fil multi-brins Ø 0.14mm² (AWG 26) Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	7	IP67	2 Brass, nickel plated Messing, vernickelt Laiton, nickelé	B1 Blue Blau Bleu	R521 80 mcd	 White Weiss Blanc	Z	230	5	
	8	IP68	5 Stainless steel Edelstahl Acier inoxydable	C1 Clear Klar Claire	W55N 22'000 mcd					
			6 Stainless steel, blackened Edelstahl, geschwärzt Acier inoxydable, noirci	G1 Green Grün Vert	W50N 2'320 mcd					
	8	IP68	9 Brass, olive drab** Messing, olivebraun** Laiton, olivebrun**	R1 Red Rot Rouge	RGKW common cathode only series 343, 348					 Red-Green Rot-Grün Rouge-Vert
W3 White Weiss Blanc				RGVW common anode only series 343, 348						

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C / 230V Operating Temperature -30° to +65°C

RoHS compliant / ** except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

different LED's of the SLOAN range can be built in

*refer to installation instructions for 230V version in chapter „G“

Réserve de modifications de toutes les données techniques

34..

