

## Indicator lights with reflector

rear mounting, rotation proof  
Option: waterproof IP64 / IP67 / IP68

## Signalleuchten mit Reflektor

von hinten montierbar, verdrehsicher  
Option: wasserdicht IP64 / IP67 / IP68

## Voyants lumineux avec réflecteur

montage par l'arrière, anti-rotation  
Option: étanche IP64 / IP67 / IP68

## Series 133R / 134R / 138R



3D Step-file  
available on request



134R8V1NR301B 138R811N010Y301B

### Further specifications and options in section „F-H“ / Weitere Spezifikationen und Optionen in Kapitel „F-H“ / Autres spécifications et options au chapitre „F-H“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires		Light source Lichtquelle Source lum.	Voltage Spannung Tension			
Terminals Anschlüsse Raccords	Protection Schutzart Protection	Surface Oberfläche Surface				LED Ø 3mm	Code	V	mA
<b>133R</b>  LED terminals LED-Anschlüsse Fils des LEDs	4	IP64	<b>U</b>	Brass, blackened Messing, geschwärzt Laiton, noirci	<b>1</b> Lock washer Fächer- scheibe Rondelle de freinage  <b>N</b> Ornamen- tal nut Ziermutter Écrou décoratif  	<b>Y33U</b> 4'200 mcd <b>Y30U</b> 1'200 mcd <b>Y301</b> 30 mcd 	<b>0</b>	without ohne sans	<b>A</b> 5 20 <b>B</b> 12 20 <b>D</b> 24 20 <b>E</b> 28 20
	7	IP67	<b>V</b>	Brass, nickel plated Messing, vernickelt Laiton, nickelé					
	8	IP68				<b>2</b> Ornamen- tal washer Zier- scheibe Rondelle décoratif  	<b>B71G</b> 6'220 mcd <b>B41G</b> 1'160 mcd 		
<b>134R</b>  Solder lugs Lötösen Contact à souder	4	IP64	<b>1</b>	Brass, blackened Messing, geschwärzt Laiton, noirci	<b>1</b> Lock washer Fächer- scheibe Rondelle de freinage  <b>N</b> Ornamen- tal nut Ziermutter Écrou décoratif  	<b>G41N</b> 17'600 mcd <b>G51N</b> 10'320 mcd <b>G301</b> 40 mcd 	<b>D</b>	24	<b>E</b> 28 20
	7	IP67	<b>2</b>	Brass, nickel plated Messing, vernickelt Laiton, nickelé					
	8	IP68				<b>2</b> Ornamen- tal washer Zier- scheibe Rondelle décoratif  	<b>R30U</b> 5'500 mcd <b>R301</b> 8 mcd <b>R33U</b> 2'500 mcd 		
<b>138R</b>  Stranded wire Litze Fil multi-brins Ø 0.14mm² (AWG 26)	4	IP64	<b>1</b>	Brass, blackened Messing, geschwärzt Laiton, noirci	<b>1</b> Lock washer Fächer- scheibe Rondelle de freinage  <b>N</b> Ornamen- tal nut Ziermutter Écrou décoratif  	<b>010</b> Standard 100mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	<b>010</b>	Standard 100mm	<b>W37N</b> 13'350 mcd <b>W36N</b> 6'900 mcd <b>W32N</b> 3'745 mcd 
	7	IP67	<b>2</b>	Brass, nickel plated Messing, vernickelt Laiton, nickelé					
	8	IP68				<b>2</b> Ornamen- tal washer Zier- scheibe Rondelle décoratif  			

Operating Temperature -30° to +85°C / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant / \*\* except surface option 9 (none RoHS)

Specifications are subject to change without notice

Änderungen die dem technischen Fortschritt dienen, sind vorbehalten

Réserve de modifications de toutes les données techniques

**13..R**

