


Flexiprint silicone IP64

5060 PLCC6, RGB, high bright

FPL-F02B-250

Specifications

Voltage	12V
Current	3 x 1A
Wattage	14.4W/m (3 x 4.8W/m)
Number of LEDs	150pcs
Length of stripe	2.5m
Viewing angle	120°
Min. bending radius (edges/corners)	60mm
Operating temperature	-15 to +40°C
Storage temperature	-25 to +60°C
CE/RoHS compliant	






Benefits

Adhesive tape on backside

About IP64


Splash proof from all directions.
 Test requirements according to IEC 60598-1 (9.2.5) for 20Min.
 No protection against UV, salt water/smog and chlorine!
 IP protection is no longer applicable after cutting!
 Cable/connector meets only IP64 protection!

Electrical and optical characteristics (Ta=25°C)

Part number	Colour	Wavelength	Intensity lm/m
FPL-F02B-250	 red	620nm	115
	 green	520nm	245
	 blue	470nm	51

the reduction of light output for IP64 products is about -10%, due to silicone acting as a filter

Dimensions



Thickness: 3mm +1
 Thickness endings: 4mm

1. All dimensions are in millimetres
2. Length tolerance ±1%
3. All strandet wires cross section 0.2mm² AWG #24
4. Specifications are subject to change without notice

Please also take note of our **General Information for Flexiprint and LED Modules**