

R0-Series 18.5 x 15.8mm









High bright (LED type 2835)

Specifications

Dimensions	18.5 x 15.8 mm (W x H)
Voltage	24V
Current	~1A/m
Wattage	23W/m
Brightness	~ 1400lm/m
Number of LED's	112pcs/m
Operating Temperature	-20°~+40°C
Storage Temperature	-40°~+80°C
Viewing Angle	~110°
CE	
RoHS compliant	



Further technical information in „Profile Specifications“

Profile Type	Colour of Profile	Length of Profile (incl. end-caps)	Cover	Cable Input	Cable Output	Cable Length	Connector	Mounting Clip	Lightsource	Voltage				
R0	1 natural anodized other colours on request	027 270mm*	1 white diffused	1 lateral cable input 	1 lateral cable output 	050 50cm other length on request	0 without connector (wire leads) 1 with DC-Jack  input output	0 without clips 1 with clips 2 clips per unit	N01  warm-white 2800-3500K	D 24VDC				
		039 390mm*	2 clear								2 without cable 	2 with snap-in connector  input output	S01  natural-white 3800-4500K	
		046 460mm*												W01  cold-white 5500-6500K
		058 580mm*												
		064 640mm*												
		082 820mm*												
		089 890mm*												
		095 950mm* other length on request *Tolerance: +/-2mm												



Warning: Do not connect more than 3m in a row



1. All dimensions are in millimetres
2. Tolerance is ±0.25mm unless otherwise specified
3. Specifications are subject to change without notice

Please also take note of our **General Information for LED Products**